

**Description**

Fastener Length: 3/4", Thread: 10-32A, Thread Length: 7/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	STD2180D45
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-467-7555
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

## P/N STD2180D45 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.220 Inches Nominal
<b>Fastener Length:</b>	0.733 Inches Minimum And 0.753 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.337 Inches Minimum And 0.387 Inches Maximum
<b>Grip Diameter:</b>	0.1898 Inches Minimum And 0.1904 Inches Maximum
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.450 Inches Minimum And 0.513 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32a
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4967 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Std 2167 Cagc 99995 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/STD2180D45> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.