

Description

Fastener Length: 3/4", Thread: 10-32A, Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	STD2180D45
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-467-7555
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N STD2180D45 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.220 Inches Nominal
Fastener Length:	0.733 Inches Minimum And 0.753 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.387 Inches Maximum
Grip Diameter:	0.1898 Inches Minimum And 0.1904 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.450 Inches Minimum And 0.513 Inches Maximum
Thread Quantity Per Inch:	32a
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Std 2167 Cagc 99995 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/STD2180D45> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.