



Military-Fasteners.com

P/N STD3053-35

Description

Fastener Length: 1/4", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	STD305335
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-282-5509
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N STD3053-35 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.198 Inches Minimum And 0.260 Inches Maximum
Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.209 Inches Minimum And 0.229 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	4
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8740
Screw Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/STD3053-35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.