

P/N STD3060-01

Description

Fastener Length: 3/16", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	STD306001
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-013-7761
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight	093486 Bolts nuts Or Screws Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N STD3060-01 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.126 Inches Minimum
Fastener Length:	0.188 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.230 Inches Nominal
Width Between Flats:	0.212 Inches Minimum And 0.220 Inches Maximum
Extended Washer Diameter:	0.312 Inches Nominal
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Flats
Surface Finish:	32.0 Microinches Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/STD3060-01 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.