

# **P/N STD3060-05**

### **Description**

Fastener Length: 7/16", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 23/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	STD306005
Minimum Qty (MOQ):	1
NSN:	5306-00-102-4562
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N STD3060-05 Specifications**

3a
Right-hand
0.346 Inches Minimum And 0.366 Inches Maximum
0.438 Inches Nominal
Double Hexagon W/hole
0.230 Inches Nominal
0.212 Inches Minimum And 0.220 Inches Maximum
0.312 Inches Nominal
0.040 Inches Minimum And 0.050 Inches Maximum
0.047 Inches Nominal
0.190 Inches
4
Drilled
Finished Head
32
130000 Pounds Per Square Inch
85000 Pounds Per Square Inch
Double Hexagon Longitudinal Hole
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
Iron Alloy 660 Overall
Ams 5732 Assn Std Single Material Response Overall
Unjf

### **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/STD3060-05">https://military-fasteners.com/bolts/machine+bolts/STD3060-05</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.