

P/N STD3060-06

Description

Fastener Length: 1/2", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| SKU / Model: | STD306006 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-111-3837 |
| Schedule B: | 7318.15.8085 |
| | |

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N STD3060-06 Specifications

| Thread Class: | 3a |
|---------------------------------------|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.400 Inches Minimum |
| Fastener Length: | 0.500 Inches Nominal |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.230 Inches Nominal |
| Width Between Flats: | 0.212 Inches Minimum And 0.220 Inches Maximum |
| Extended Washer Diameter: | 0.312 Inches Nominal |
| Extended Washer Thickness: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Hole Diameter: | 0.047 Inches Nominal |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.072 Inches Minimum And 0.092 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Hole Configuration Style: | Double Hexagon Longitudinal Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/STD3060-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.