

# **P/N STD3060-09**

### **Description**

Fastener Length: 11/16", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 39/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	STD306009
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-013-7760
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N STD3060-09 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.596 Inches Minimum And 0.612 Inches Maximum
Fastener Length:	0.688 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.230 Inches Nominal
Width Between Flats:	0.212 Inches Minimum And 0.220 Inches Maximum
Extended Washer Diameter:	0.312 Inches Nominal
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Flats
Surface Finish:	32.0 Microinches Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/STD3060-09">https://military-fasteners.com/bolts/machine+bolts/STD3060-09</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.