

Description

Fastener Length: 15/16", Hole Diameter: ", Thread: 10-32, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	STD306013
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-107-4757
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N STD3060-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.620 Inches Minimum And 0.700 Inches Maximum
Fastener Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.220 Inches Minimum And 0.240 Inches Maximum
Width Between Flats:	0.212 Inches Minimum And 0.220 Inches Maximum
Extended Washer Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Hole Diameter:	0.060 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.248 Inches Minimum And 0.308 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Criticality Code Justification:	Test
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall

Test Data Document:	91547-+6808 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/STD3060-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.