

Description

Fastener Length: 3/8", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 9/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	STD306104
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-083-1580
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N STD3061-04 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Minimum And 0.296 Inches Maximum
Fastener Length:	0.375 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.260 Inches Nominal
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.079 Inches Minimum And 0.099 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/STD3061-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.