

P/N STD3061-09

Description

Fastener Length: 11/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 39/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: STD306109

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-192-0544

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N STD3061-09 Specifications

Thread Class: 3a	
Thread Direction: Right-hand	
Thread Length: 0.589 Inches Minimum And 0.609 Inches Maximum	
Fastener Length: 0.688 Inches Nominal	
Head Style: Double Hexagon W/hole	
Head Height: 0.260 Inches Nominal	
Width Between Flats: 0.243 Inches Minimum And 0.251 Inches Maximum	
Extended Washer Diameter: 0.375 Inches Nominal	
Extended Washer Thickness: 0.060 Inches Minimum And 0.070 Inches Maximum	
Hole Diameter: 0.047 Inches Nominal	
Nominal Thread Diameter: 0.250 Inches	
Grip Length: 0.079 Inches Minimum And 0.099 Inches Maximum	
Hole Quantity: 4	
Hole Type: Drilled	
Features Provided: Finished Head	
Thread Quantity Per Inch: 28	
Minimum Tensile Strength: 130000 Pounds Per Square Inch	
Hardness Rating: 248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall	
Minimum Yield Strength: 85000 Pounds Per Square Inch	
Hole Configuration Style: Double Hexagon Longitudinal Hole	
Surface Finish: 32.0 Microinches Bearing Surface Of Head	
Surface Finish: 32.0 Microinches Grip	
Surface Finish: 32.0 Microinches Threads	
Surface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 Overall	

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/STD3061-09 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.