

# P/N STD3061-13

### **Description**

Fastener Length: 15/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 13/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: STD306113

Minimum Qty (MOQ): 5 EA

NSN: 5306-01-200-6250

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N STD3061-13 Specifications**

| Thread Class:                         | 3a  |
|---------------------------------------|---|
| Thread Direction:                     | Right-hand  |
| Thread Length:                        | 0.740 Inches Minimum And 0.820 Inches Maximum                       |
| Fastener Length:                      | 0.928 Inches Minimum And 0.948 Inches Maximum                       |
| Head Style:                           | Double Hexagon W/hole   |
| Head Height:                          | 0.260 Inches Nominal  |
| Width Between Flats:                  | 0.243 Inches Minimum And 0.251 Inches Maximum                       |
| Extended Washer Diameter:             | 0.375 Inches Nominal  |
| Extended Washer Thickness:            | 0.060 Inches Minimum And 0.070 Inches Maximum                       |
| Hole Diameter:                        | 0.047 Inches Nominal  |
| Nominal Thread Diameter:              | 0.250 Inches  |
| Grip Length:                          | 0.128 Inches Minimum And 0.188 Inches Maximum                       |
| Hole Quantity:                        | 4   |
| Hole Type:                            | Drilled   |
| Features Provided:                    | Finished Head   |
| Thread Quantity Per Inch:             | 28  |
| Minimum Tensile Strength:             | 130000 Pounds Per Square Inch                                       |
| Hardness Rating:                      | 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall |
| Minimum Yield Strength:               | 85000 Pounds Per Square Inch  |
| Hole Configuration Style:             | Double Hexagon Longitudinal Hole                                    |
| Surface Finish:                       | 32.0 Microinches Bearing Surface Of Head                            |
| Surface Finish:                       | 32.0 Microinches Grip   |
| Surface Finish:                       | 32.0 Microinches Threads  |
| Material:                             | Iron Alloy 660 Overall  |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall                  |
| Thread Series Designator:             | Unjf  |
|                                       |   |

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/STD3061-13">https://military-fasteners.com/bolts/machine+bolts/STD3061-13</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.