

Description

Fastener Length: 59/64", Thread: 1/4-28, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	STSBG003A04U006
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-492-7022
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N STSBG003A04U006 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.521 Inches Minimum And 0.571 Inches Maximum
Fastener Length:	0.906 Inches Minimum And 0.936 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.254 Inches Nominal
Width Between Flats:	0.304 Inches Minimum And 0.315 Inches Maximum
Extended Washer Diameter:	0.465 Inches Minimum And 0.475 Inches Maximum
Extended Washer Thickness:	0.042 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	260000 Pounds Per Square Inch
Material:	Steel Comp H11 Overall
Material Document And Classification:	Stsbs003,fscm 98897 Mfr Ref Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Stsbs,fscm 98897 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/STSBG003A04U006> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.