

Description

Fastener Length: 2-3/32", Thread: 3/8-24, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	STSBG004A06U024
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-321-4736
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N STSBG004A06U024 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.558 Inches Minimum And 0.608 Inches Maximum
Fastener Length:	2.068 Inches Minimum And 2.098 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.322 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.091 Inches Nominal
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.490 Inches Minimum And 1.510 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	260000 Pounds Per Square Inch
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Surface Treatment Document And Classification:	Ams 2416 Assn Std All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/STSBG004A06U024> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.