

Description

Length: 6-5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	TA12C79HR80
Minimum Qty (MOQ):	1 EA
NSN:	5340-01-169-5667
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N TA12C79HR80 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Fuel Resistant And Oil Resistant
Overall Length:	6.669 Inches Minimum And 6.699 Inches Maximum
Overall Width:	0.750 Inches Nominal
Diameter:	0.281 Inches Nominal
Material Thickness:	0.050 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	3.0225 Inches Minimum And 3.0375 Inches Maximum
Distance From Loop Center To Tongue End:	3.3345 Inches Minimum And 3.3495 Inches Maximum
Loop Inside Diameter:	5.000 Inches Nominal
Special Features:	Heat-shrinkable Polyolefin Sleeve,mil-i-23053/5,class 2,clear,shrunk Over Cushion
Material:	Rubber Fluorosilicone Class Fq Cushion
Material:	Steel Comp 321 Band Or Steel Comp 347 Band
Material Document And Classification:	Ams 5510 Assn Std 1st Material Response Band Or Ams 5512 Assn Std 2nd Material Response Band
Material Document And Classification:	Mil-r-25988,class 2,grade 50,type 2 Mil Spec Single Material Response Cushion Or Dow Corning Ls2332u(usaf) Mfr Ref Single Material Response Cushion
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Saddle Mount

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/TA12C79HR80> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.