

**Description**

Length: 6-5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	TA12C79HR80
Minimum Qty (MOQ):	1 EA
NSN:	5340-01-169-5667
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N TA12C79HR80 Specifications

<b>Tongue Hole Type:</b>	Round, Unthreaded
<b>Cushioning Environmental Protection:</b>	Fuel Resistant And Oil Resistant
<b>Overall Length:</b>	6.669 Inches Minimum And 6.699 Inches Maximum
<b>Overall Width:</b>	0.750 Inches Nominal
<b>Diameter:</b>	0.281 Inches Nominal
<b>Material Thickness:</b>	0.050 Inches Nominal
<b>Center To Center Distance Between Loop And Mounting Hole:</b>	3.0225 Inches Minimum And 3.0375 Inches Maximum
<b>Distance From Loop Center To Tongue End:</b>	3.3345 Inches Minimum And 3.3495 Inches Maximum
<b>Loop Inside Diameter:</b>	5.000 Inches Nominal
<b>Special Features:</b>	Heat-shrinkable Polyolefin Sleeve,mil-i-23053/5,class 2,clear,shrunk Over Cushion
<b>Material:</b>	Rubber Fluorosilicone Class Fq Cushion
<b>Material:</b>	Steel Comp 321 Band Or Steel Comp 347 Band
<b>Material Document And Classification:</b>	Ams 5510 Assn Std 1st Material Response Band Or Ams 5512 Assn Std 2nd Material Response Band
<b>Material Document And Classification:</b>	Mil-r-25988,class 2,grade 50,type 2 Mil Spec Single Material Response Cushion Or Dow Corning Ls2332u(usaf) Mfr Ref Single Material Response Cushion
<b>Surface Treatment:</b>	Passivate Band
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Band
<b>Style Designator:</b>	Saddle Mount

## How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/TA12C79HR80> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.