

Description

Fastener Length: 1-15/64", Thread Size: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	TLC881612E
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-349-1862
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N TLC881-6-12E Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.224 Inches Minimum And 1.249 Inches Maximum
Head Style:	Err-090
Shank Diameter:	0.3690 Inches Nominal
Shank Style:	Pin-rivet, Tapered, Threaded
Head Major Diameter:	0.681 Inches Maximum
Tip Diameter:	0.3571 Inches Nominal
Lubrication:	Dry Film And Cetyl Alcohol
Grip Length:	0.740 Inches Minimum And 0.755 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLC881-6-12E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.