

**Description**

Fastener Length: 1-15/64", Thread Size: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | TLC881612E                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5320-01-349-1862                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



\* See page 2 for technical characteristics

## P/N TLC881-6-12E Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Fastener Length:</b>                               | 1.224 Inches Minimum And 1.249 Inches Maximum      |
| <b>Head Style:</b>                                    | Err-090  |
| <b>Shank Diameter:</b>                                | 0.3690 Inches Nominal                              |
| <b>Shank Style:</b>                                   | Pin-rivet, Tapered, Threaded                       |
| <b>Head Major Diameter:</b>                           | 0.681 Inches Maximum                               |
| <b>Tip Diameter:</b>                                  | 0.3571 Inches Nominal                              |
| <b>Lubrication:</b>                                   | Dry Film And Cetyl Alcohol                         |
| <b>Grip Length:</b>                                   | 0.740 Inches Minimum And 0.755 Inches Maximum      |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Nominal Thread Size:</b>                           | 0.375 Inches                                       |
| <b>Shear Strength:</b>                                | 95000 Single Pounds Per Square Inch                |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal                              |
| <b>Material:</b>                                      | Iron Alloy 660 Overall                             |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall                                  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLC881-6-12E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.