

Description

Fastener Length: 53/64", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	TLD11057E
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-073-5090
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N TLD110-5-7E Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.808 Inches Minimum And 0.833 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.3403 Inches Nominal
<b>Shank Style:</b>	Pin-rivet, Tapered, Threaded
<b>Head Major Diameter:</b>	0.508 Inches Maximum
<b>Tip Diameter:</b>	0.3345 Inches Nominal
<b>Lubrication:</b>	Dry Film And Cetyl Alcohol
<b>Grip Length:</b>	0.427 Inches Minimum And 0.442 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	220000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.312 Inches
<b>Shear Strength:</b>	125000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams 5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLD110-5-7E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.