

Description

Fastener Length: 0-63/64", Thread Size: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	TLD11088E
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-160-5741
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N TLD110-8-8E Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.975 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.5400 Inches Nominal
Shank Style:	Pin-riquet, Tapered, Threaded
Head Major Diameter:	0.803 Inches Maximum
Tip Diameter:	0.5338 Inches Nominal
Lubrication:	Cetyl Alcohol And Dry Film
Grip Length:	0.490 Inches Minimum And 0.505 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Nominal Thread Size:	0.500 Inches
Shear Strength:	125000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1725 Professional/industrial Association Standard

How to Order

Order this taper bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLD110-8-8E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.