

Description

Fastener Length: 27/32", Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	TLD96657E20
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-268-5597
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N TLD966-5-7E-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.833 Inches Minimum And 0.858 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.3547 Inches Nominal
Shank Style:	Pin-riquet, Tapered, Threaded
Head Major Diameter:	0.522 Inches Maximum
Tip Diameter:	0.3489 Inches Nominal
Lubrication:	Dry Film And Cetyl Alcohol
Grip Length:	0.427 Inches Minimum And 0.442 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Nominal Thread Size:	0.164 Inches
Shear Strength:	125000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Slot 0.200 In. L And 0.060 In. W
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLD966-5-7E-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.