

Description

Fastener Length: 3/4", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	TLV10038E
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-281-3351
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N TLV100-3-8E Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.780 Inches Nominal
Head Style:	Flush Countersunk
Shank Diameter:	0.2001 Inches Nominal
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.317 Inches Maximum
Grip Length:	0.500 Inches Nominal
Nominal Thread Size:	0.190 Inches
Countersink Angle:	100.0 Degrees Nominal
Special Features:	0.192 In. Second Shank Dia,dry Film Lubricant Plus Cetyl Alcohol
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLV100-3-8E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.