

Description

Fastener Length: 3/4", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | TLV10038E |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-00-281-3351 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N TLV100-3-8E Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.780 Inches Nominal |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.2001 Inches Nominal |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.317 Inches Maximum |
| Grip Length: | 0.500 Inches Nominal |
| Nominal Thread Size: | 0.190 Inches |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | 0.192 In. Second Shank Dia,dry Film Lubricant Plus Cetyl Alcohol |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLV100-3-8E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.