

Description

Fastener Length: 1-1/64", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	TLV100411E
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-280-3581
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



\* See page 2 for technical characteristics

# P/N TLV100-4-11E Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.020 Inches Nominal
Head Style:	Flush Countersunk
Shank Diameter:	0.2754 Inches Nominal
Shank Style:	Pin-rivet, Tapered, Threaded
Head Major Diameter:	0.426 Inches Maximum
Tip Diameter:	0.2642 Inches Nominal
Lubrication:	Dry Film And Cetyl Alcohol
Grip Length:	0.687 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.250 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLV100-4-11E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.