

# P/N TLV100-4-12E

## **Description**

Fastener Length: 1-5/64", Thread Size: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

### NAS1724V4-12E

SKU / Model: TLV100412E

Minimum Qty (MOQ): 5

NSN: 5320-00-280-3582

Schedule B: 8108.90.3060

ECCN: 9A991

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N TLV100-4-12E Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.082 Inches Nominal
Head Style:	Flush Countersunk
Shank Diameter:	0.2754 Inches Nominal
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.426 Inches Maximum
Grip Length:	0.750 Inches Nominal
Nominal Thread Size:	0.250 Inches
Countersink Angle:	100.0 Degrees Nominal
Special Features:	0.263 In. Second Shank Dia,dry Film Lubricant,plus Cetyl Alcohol
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1724 Professional/industrial Association Standard

## **How to Order**

Order this tl bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/TLV100-4-12E">https://military-fasteners.com/bolts/machine+bolts/TLV100-4-12E</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.