

P/N TLV100-4-12E

Description

Fastener Length: 1-5/64", Thread Size: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1724V4-12E

SKU / Model: TLV100412E

Minimum Qty (MOQ): 5

NSN: 5320-00-280-3582

Schedule B: 8108.90.3060

ECCN: 9A991

National Motor Freight: 136500, Metal Noi / Metal Alloys Noi



^{*} See page 2 for technical characteristics

P/N TLV100-4-12E Specifications

| Thread Class: | 3a |
|---------------------------------------|--|
| Thread Direction: | Right-hand |
| Fastener Length: | 1.082 Inches Nominal |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.2754 Inches Nominal |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.426 Inches Maximum |
| Grip Length: | 0.750 Inches Nominal |
| Nominal Thread Size: | 0.250 Inches |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | 0.263 In. Second Shank Dia,dry Film Lubricant,plus Cetyl Alcohol |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1724 Professional/industrial Association Standard |

How to Order

Order this tl bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/TLV100-4-12E and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.