

Description

Fastener Length: 1-11/32", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | TLV100416 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-00-913-7448 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N TLV100-4-16 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 1.322 Inches Minimum And 1.347 Inches Maximum |
| Head Style: | Flush Countersunk |
| Shank Diameter: | 0.2754 Inches Nominal |
| Shank Style: | Pin-rivet, Tapered, Threaded |
| Head Major Diameter: | 0.426 Inches Maximum |
| Tip Diameter: | 0.2577 Inches Nominal |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.990 Inches Minimum And 1.005 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Nominal Thread Size: | 0.250 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLV100-4-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.