

Description

Fastener Length: 37/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	TLV10044E
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-288-3077
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N TLV100-4-4E Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.582 Inches Nominal
Head Style:	Flush Countersunk
Shank Diameter:	0.2624 Inches Nominal
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.413 Inches Maximum
Grip Length:	0.250 Inches Nominal
Nominal Thread Size:	0.250 Inches
Countersink Angle:	100.0 Degrees Nominal
Special Features:	0.2600 In. Second Shank Dia. And Lubrication,dry Film
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this taper bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLV100-4-4E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.