

**Description**

Fastener Length: 37/64", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	TLV10044E
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-288-3077
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N TLV100-4-4E Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.582 Inches Nominal
<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.2624 Inches Nominal
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.413 Inches Maximum
<b>Grip Length:</b>	0.250 Inches Nominal
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	0.2600 In. Second Shank Dia. And Lubrication,dry Film
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this taper bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLV100-4-4E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.