

Description

Fastener Length: 1-25/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	TLV100516
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-476-7396
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N TLV100-5-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.371 Inches Minimum And 1.396 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.3403 Inches Nominal
Shank Style:	Pin-rivet, Tapered, Threaded
Head Major Diameter:	0.508 Inches Maximum
Tip Diameter:	0.3228 Inches Nominal
Lubrication:	Cetyl Alcohol
Grip Length:	0.990 Inches Minimum And 1.005 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.312 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1724 Professional/industrial Association Standard

How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLV100-5-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.