

**Description**

Fastener Length: 1-25/64", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	TLV100516
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-476-7396
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N TLV100-5-16 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.371 Inches Minimum And 1.396 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.3403 Inches Nominal
<b>Shank Style:</b>	Pin-rivet, Tapered, Threaded
<b>Head Major Diameter:</b>	0.508 Inches Maximum
<b>Tip Diameter:</b>	0.3228 Inches Nominal
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.990 Inches Minimum And 1.005 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.312 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1724 Professional/Industrial Association Standard

## How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLV100-5-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.