

Description

Fastener Length: 27/32", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	TLV13038E
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-046-3352
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N TLV130-3-8E Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.822 Inches Minimum And 0.847 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.2209 Inches Nominal
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.337 Inches Maximum
Grip Length:	0.490 Inches Minimum And 0.505 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Dry Film And Cetyl Alcohol Lubricants,0.2133 In. Second Shank Diameter
Material:	Titanium Alloy Uns R56400 Overall
Thread Series Designator:	Unjf

How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLV130-3-8E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.