

Description

Fastener Length: 1-1/32", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	TLV130510E
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-094-9150
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N TLV130-5-10E Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.021 Inches Minimum And 1.046 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.3547 Inches Nominal
Shank Style:	Pin-rivet, Tapered, Threaded
Head Major Diameter:	0.522 Inches Maximum
Tip Diameter:	0.3449 Inches Nominal
Lubrication:	Cetyl Alcohol And Dry Film
Grip Length:	0.615 Inches Minimum And 0.630 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.312 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this tl bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/TLV130-5-10E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.