

Description

Bolt part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	UB100EV0609
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-488-2878
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N UB100-EV06-09 Specifications

Head Style:	Countersunk (tubular)
Shank Diameter:	0.198 Inches Nominal
Shank Style:	Closed End Solid-core
Head Major Diameter:	0.386 Inches Nominal
Expansion Device:	Serrated Stem-type W
End Item Identification:	F/2-22 Raptor
Grip Length:	0.531 Inches Minimum And 0.595 Inches Maximum
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Bolt Blind
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 316 Collar
Material:	Titanium Alloy Stem
Material Document And Classification:	Ams 5737 National Std/spec Single Material Response Sleeve
Material Document And Classification:	Ams 5690 National Std/spec Single Material Response Collar
Material Document And Classification:	Mil-r-9047 Mil Spec Single Material Response Stem
Surface Treatment:	Passivate Collar
Surface Treatment:	Passivate Sleeve

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/UB100-EV06-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.