

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	UR175L
Minimum Qty (MOQ):	20
NSN:	5325-01-126-8978
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N UR-175-L Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	1.591 Inches Minimum And 1.611 Inches Maximum
Casehardening Indicator:	Not Casehardened
Outside Diameter:	1.827 Inches Minimum And 1.847 Inches Maximum
Major Thickness:	0.029 Inches Minimum And 0.033 Inches Maximum
Ring Style:	Special
Usage Design:	Internal
Strength Rating:	221000.0 Pounds Per Square Inch Minimum Tensile
Material:	Steel, Fed Std 66, Comp 1070 Or Steel, Fed Std 66, Comp 1072 Or Steel, Fed Std 66, Comp 1074 Or Steel, Fed Std 66, Comp 1075 Or Steel, Fed Std 66, Comp 1078 Or Steel, Fed Std 66, Comp 1080 Or Steel, Fed Std 66, Comp 1084 Or Steel, Fed Std 66, Comp 1085 Or Steel, Fed Std 66, Comp 1086 Or Steel, Fed Std 66, Comp 1090
Material:	Steel Comp 1070 Or Steel Comp 1572 Or Steel Comp 1074 Or Steel Comp 1075 Or Steel Comp 1078 Or Steel Comp 1080 Or Steel Comp 1070 Or Steel Comp 1085 Or Steel Comp 1086 Or Steel Comp 1090
Material Document And Classification:	Fed Std 66, Comp 1070 Fed Std 1st Material Response And Fed Std 66, Comp 1072 Fed Std 2nd Material Response And Fed Std 66, Comp 1074 Fed Std 3rd Material Response And Fed Std 66, Comp 1075 Fed Std 4th Material Response And Fed Std 66, Comp 1078 Fed Std 5th Material Response And Fed Std 66, Comp 1080 Fed Std 6th Material Response And Fed Std 66, Comp 1084 Fed Std 7th Material Response And Fed Std 66, Comp 1085 Fed Std 8th Material Response And Fed Std 66, Comp 1086 Fed Std 9th Material Response And Fed Std 66, Comp 1090 Fed Std 10th Material Response
Surface Treatment:	Phosphate Zinc
Surface Treatment Document And Classification:	Dod-p-16232, Type Z, Class 2 Def Stan/spec Single Treatment Response
Surface Treatment:	Phosphate, Dod-p-16232, Type Z, Class 2

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/UR-175-L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.