

Description

Retaining Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	UR700S
Minimum Qty (MOQ):	5 EA
NSN:	5325-01-326-1353
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N UR-700-S Specifications

Cross-sectional Shape Style:	Rectangular
Inside Diameter:	6.717 Inches Minimum And 6.762 Inches Maximum
Casehardening Indicator:	Not Casehardened
Outside Diameter:	7.247 Inches Minimum And 7.292 Inches Maximum
Major Thickness:	0.059 Inches Minimum And 0.063 Inches Maximum
Ring Style:	Special
Usage Design:	Internal
Strength Rating:	175000.0 Pounds Per Square Inch Minimum Tensile
Material:	Steel, Sae 302 Or Steel, Aisi 302 Or Steel, Mil-s-5059, Type 302 Or Steel, Ams 5688 Or Steel, Qq-s-766, Class 302
Material:	Steel Comp 302 Or Steel Comp 302 Or Steel Comp 302 Or Steel Comp 302 Or Steel Comp 302
Material Document And Classification:	Sae 302 Assn Std 1st Material Response And Aisi 302 Assn Std 2nd Material Response And Mil-s-5059, Type 302 Mil Spec 3rd Material Response And Ams 5688 Assn Std 4th Material Response And Qq-s-766, Class 302 Fed Spec 5th Material Response

How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/UR-700-S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.