

**Description**

Retaining Ring part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	VH62S02
Minimum Qty (MOQ):	40 EA
NSN:	5325-00-455-2564
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N VH-62-S02 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Inside Diameter:</b>	0.566 Inches Minimum And 0.579 Inches Maximum
<b>Casehardening Indicator:</b>	Not Casehardened
<b>Outside Diameter:</b>	0.656 Inches Minimum And 0.669 Inches Maximum
<b>Major Thickness:</b>	0.0165 Inches Minimum And 0.0195 Inches Maximum
<b>Ring Style:</b>	Special
<b>Usage Design:</b>	Internal
<b>Strength Rating:</b>	210000.0 Pounds Per Square Inch Minimum Tensile
<b>Material:</b>	Steel, Sae 302 Or Steel, Aisi 302 Or Steel, Mil-s-5059, Type 302 Or Steel, Ams 5688 Or Steel, Qq-s-766, Class 302
<b>Material:</b>	Steel Comp 302 Or Steel Comp 302 Or Steel Comp 302 Or Steel Comp 302 Or Steel Comp 302
<b>Material Document And Classification:</b>	Sae 302 Assn Std 1st Material Response And Aisi 302 Assn Std 2nd Material Response And Mil-s-5059, Type 302 Mil Spec 3rd Material Response And Ams 5688 Assn Std 4th Material Response And Qq-s-766, Class 302 Fed Spec 5th Material Response

## How to Order

Order this retaining ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/VH-62-S02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.