

## P/N VT1051-3-7

## **Description**

Fastener Length: 23/32", Thread: 10-32, Thread Length: 19/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: VT105137
Minimum Qty (MOQ): 10 EA

NSN: 5305-00-498-9730

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N VT1051-3-7 Specifications

| Thread Class:                                  | 3a  |
|--|---|
| Thread Direction:                              | Right-hand  |
| Thread Length:                                 | 0.250 Inches Minimum And 0.300 Inches Maximum                                 |
| Fastener Length:                               | 0.698 Inches Minimum And 0.728 Inches Maximum                                 |
| Head Style:                                    | Flat Countersunk  |
| Head Diameter:                                 | 0.270 Inches Minimum And 0.302 Inches Maximum                                 |
| Grip Diameter:                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum                               |
| Internal Drive Style:                          | Offset Cruciform (torque Set)   |
| Nominal Thread Diameter:                       | 0.190 Inches  |
| Grip Length:                                   | 0.428 Inches Minimum And 0.448 Inches Maximum                                 |
| Thread Quantity Per Inch:                      | 32  |
| Hardness Rating:                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall           |
| Countersink Angle:                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                |
| Material:                                      | Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall |
| Surface Treatment:                             | Cadmium Overall   |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall                 |
| Thread Series Designator:                      | Unf   |

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/VT1051-3-7">https://military-fasteners.com/screws/machine+screws/VT1051-3-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/VT1051-3-7">https://military-fasteners.com/screws/machine+screws/VT1051-3-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/VT1051-3-7">https://military-fasteners.com/screws/machine+screws/VT1051-3-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/VT1051-3-7">https://military-fasteners.com/screws/machine+screws/VT1051-3-7</a> and selecting the quantity you want then click "add to cart".