

## P/N W23-X1A1G-10

## **Description**

10 amps, single pole with white band for visible trip indication

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: W23X1A1G10

Minimum Qty (MOQ):

NSN: 5925-01-306-9601

National Motor Freight: 061300, Circuit Breaker / Switch Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N W23-X1A1G-10 Specifications

Body Style:	Single Pole Type
Bushing Length:	0.388 Inches Nominal
Body Length:	1.375 Inches Nominal
Body Width:	0.690 Inches Nominal
Case Material:	Plastic
Center To Center Distance Between Terminals Parallel To Length:	1.020 Inches Nominal
Fragility Factor:	Moderately Rugged
End Item Identification:	Nsn 2320 01 530 3843, Truck Cargo
Mounting Surface To Terminal End Distance:	2.035 Inches Nominal
Pole Quantity:	1
Arc Quenching Method:	Air
Mounting Facility Type And Quantity:	1 Threaded Bushing
Storage Type:	General Purpose Warehouse
Thread Quantity Per Inch:	24
Maximum Continuous Load Current Rating Per Pole:	10.0 Amperes Ac Single Location And 10.0 Amperes Dc Single Location
Operating Voltage Type And Rating Per Pole In Volts:	250.0 Ac Single Location And 50.0 Dc Single Location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:	1000.0 Ac Single Location And 2500.0 Dc Single Location
Circuit Protection Type:	Overcurrent Single Location
Trip Release Method:	Thermal Single Location
Trip Release Characteristic:	Time Delay Single Location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:	135.0 Single Location
Reset Method:	Manual
Main Contact Tripping Mechanism Type:	Trip Free
Manual Actuator Type And Quantity:	1 Push-pull
Actuator Function:	Trip-reset
Actuator Position Designation:	At Pole One
Internal Trip Release Configuration:	Series Trip Single Location
Nominal Thread Size:	0.375 Inches
Trip Delay Time In Seconds Per Rated Continuous Current:	6.000 Minimum At 200 Pct Single Location And 22.000 Maximum At 200 Pct Single Location
Inclosure Protection Type For Which Designed:	Humidity Resistant And Salt Spray Proof And Shock Resistant And Vibration Resistant
Trip Release Ambient Temp Rating:	25.0 Deg Celsius Nominal Single Location

Frequency In Hertz:	400.0 Single Location
Unpackaged Unit Weight:	2.000 Ounces
Thread Series Designator:	Unf
Terminal Type And Quantity:	2 Tab W/screw

## **How to Order**

Order this circuit breaker from our inventory online by visiting <a href="https://military-fasteners.com/electrical/circuit+breakers/W23-X1A1G-10">https://military-fasteners.com/electrical/circuit+breakers/W23-X1A1G-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/electrical/circuit+breakers/W23-X1A1G-10">https://military-fasteners.com/electrical/circuit+breakers/W23-X1A1G-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/electrical/circuit+breakers/W23-X1A1G-10">https://military-fasteners.com/electrical/circuit+breakers/W23-X1A1G-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/electrical/circuit+breakers/W23-X1A1G-10">https://military-fasteners.com/electrical/circuit+breakers/W23-X1A1G-10</a> and selecting the quantity of the property of the