

Description

2 amps, single pole with red band for visible trip indication

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | W58XC4C12A2 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5925-01-042-7584 |
| National Motor Freight: | 061300, Circuit Breaker / Switch Noi |

NO IMAGE
AVAILABLE

P/N W58-XC4C12A-2 Specifications

| | |
|--|---|
| Body Style: | Single Pole Type |
| Bushing Length: | 0.300 Inches Nominal |
| Body Length: | 1.375 Inches Nominal |
| Body Width: | 0.660 Inches Nominal |
| Case Material: | Plastic |
| Center To Center Distance Between Terminals Parallel To Length: | 0.850 Inches Nominal |
| Fragility Factor: | Moderately Rugged |
| Mounting Surface To Terminal End Distance: | 1.815 Inches Nominal |
| Pole Quantity: | 1 |
| Arc Quenching Method: | Air |
| Mounting Facility Type And Quantity: | 1 Threaded Bushing |
| Storage Type: | General Purpose Warehouse |
| Thread Quantity Per Inch: | 32 |
| Maximum Continuous Load Current Rating Per Pole: | 2.0 Amperes Ac Single Location And 2.0 Amperes Dc Single Location |
| Operating Voltage Type And Rating Per Pole In Volts: | 250.0 Ac Single Location And 50.0 Dc Single Location |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: | 1000.0 Ac Single Location And 2000.0 Dc Single Location |
| Circuit Protection Type: | Overcurrent Single Location |
| Trip Release Method: | Thermal Single Location |
| Trip Release Characteristic: | Time Delay Single Location |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: | 145.0 Single Location |
| Reset Method: | Manual |
| Main Contact Tripping Mechanism Type: | Trip Free |
| Manual Actuator Type And Quantity: | 1 Push Button |
| Actuator Function: | Reset |
| Actuator Position Designation: | At Pole One |
| Internal Trip Release Configuration: | Series Trip Single Location |
| Nominal Thread Size: | 0.469 Inches |
| Trip Delay Time In Seconds Per Rated Continuous Current: | 10.000 Minimum At 200 Pct Single Location And 45.000 Maximum At 200 Pct Single Location |
| Inclosure Protection Type For Which Designed: | Shock Resistant And Vibration Resistant |
| Trip Release Ambient Temp Rating: | 25.0 Deg Celsius Nominal Single Location |
| Frequency In Hertz: | 60.0 Single Location |

| | |
|------------------------------------|--------------|
| Unpackaged Unit Weight: | 1.500 Ounces |
| Thread Series Designator: | Un |
| Terminal Type And Quantity: | 2 Screw |

How to Order

Order this circuit breaker from our inventory online by visiting <https://military-fasteners.com/electrical/circuit+breakers/W58-XC4C12A-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.