

Description

20 amps, single pole with red band for visible trip indication

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | W58XC4C12A20                         |
| Minimum Qty (MOQ):      | 1                                    |
| NSN:                    | 5925-01-250-2514                     |
| National Motor Freight: | 061300, Circuit Breaker / Switch Noi |



\* See page 2 for technical characteristics

# P/N W58-XC4C12A-20 Specifications

|   |  |
|---|--|
| Body Style:   | Single Pole Type   |
| Bushing Length:   | 0.300 Inches Nominal   |
| Body Length:  | 1.375 Inches Nominal   |
| Body Width:   | 0.660 Inches Nominal   |
| Case Material:  | Plastic  |
| Center To Center Distance Between Terminals Parallel To Length:         | 0.850 Inches Nominal   |
| Fragility Factor:   | Moderately Rugged  |
| Mounting Surface To Terminal End Distance:                              | 1.562 Inches Nominal   |
| Pole Quantity:  | 1  |
| Arc Quenching Method:   | Air  |
| Mounting Facility Type And Quantity:                                    | 1 Threaded Bushing   |
| Storage Type:   | General Purpose Warehouse  |
| Thread Quantity Per Inch:   | 32   |
| Maximum Continuous Load Current Rating Per Pole:                        | 20.0 Amperes Ac Single Location And 20.0 Amperes Dc Single Location                    |
| Operating Voltage Type And Rating Per Pole In Volts:                    | 250.0 Ac Single Location And 50.0 Dc Single Location                                   |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: | 1000.0 Ac Single Location And 2000.0 Dc Single Location                                |
| Circuit Protection Type:  | Overcurrent Single Location  |
| Trip Release Method:  | Thermal Single Location  |
| Trip Release Characteristic:  | Time Delay Single Location   |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:  | 125.0 Single Location  |
| Reset Method:   | Manual   |
| Main Contact Tripping Mechanism Type:                                   | Trip Free  |
| Manual Actuator Type And Quantity:                                      | 1 Push Button  |
| Actuator Function:  | Trip-reset   |
| Actuator Position Designation:  | At Pole One  |
| Internal Trip Release Configuration:                                    | Series Trip Single Location  |
| Nominal Thread Size:  | 0.469 Inches   |
| Trip Delay Time In Seconds Per Rated Continuous Current:                | 6.000 Minimum At 200 Pct Single Location And 30.000 Maximum At 200 Pct Single Location |
| Inclosure Protection Type For Which Designed:                           | Dustproof  |
| Trip Release Ambient Temp Rating:                                       | 30.0 Deg Celsius Nominal Single Location   |
| Frequency In Hertz:   | 60.0 Single Location   |

|                             |         |
|-----------------------------|---------|
| Terminal Type And Quantity: | 2 Screw |
|-----------------------------|---------|

## How to Order

Order this circuit breaker from our inventory online by visiting <https://military-fasteners.com/electrical/circuit+breakers/W58-XC4C12A-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.