

**Description**

Fastener Length: 9/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	XP5E
Minimum Qty (MOQ):	1
NSN:	5320-00-119-5549
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N XP5E Specifications

<b>Fastener Length:</b>	0.276 Inches Minimum And 0.296 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.050 Inches Minimum And 0.060 Inches Maximum
<b>Shank Diameter:</b>	0.156 Inches Minimum And 0.160 Inches Maximum
<b>Head Major Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.139 Inches Minimum And 0.169 Inches Maximum
<b>Material:</b>	Aluminum Alloy 2024 Stem
<b>Material:</b>	Aluminum Alloy 5056 Locking Ring
<b>Material:</b>	Aluminum Alloy 5056 Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Locking Ring
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Stem Or Chromate Stem
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/XP5E> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.