

Description

AD44ABS Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AD44ABS
Minimum Qty (MOQ):	100
NSN:	5320-01-015-6896
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE
AVAILABLE

P/N AD44ABS Specifications

Fastener Length:	0.347 Inches Minimum And 0.377 Inches Maximum
Head Style:	Universal
Head Height:	0.030 Inches Minimum And 0.040 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	140 Single Pounds Per Square Inch
Material:	Aluminum Alloy 5052 Body
Material:	Aluminum Alloy 7178 Mandrel

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/%E2%80%8BAD44ABS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.